

## TRV 700i XT



### Tech Specs

#### Engine

- Bore & Stroke (mm)102 x 85
- Engine TypeSOHC, 4-stroke, 4-valve EFI
  
- Engine displacement (cc)695
- Gas / DieselGas
- PS / KW (L7e)20,4 / 15
- PS / KW (off Road)44,6 / 32,8
- Cooling SystemLiquid with fan

#### Dimensions

- Overall length (cm/in.)248,9 / 98,6
- Overall width (cm/in.)120,7 / 47,5
- Overall height (cm/in.)127,8 / 50,3
- Wheelbase (cm/in.)147,3 / 58
- Wheelbase (Short/Long)Long Wheel Base
- Ground Clearance (cm/in.)27,9 / 11
- Dry weight375,58 / 828

#### Powertrain

- TransmissionAutomatic CVT with EBS
- Gear SelectionL / H / N / R
- Drive System2/4 WD + Electric Diff. Lock
- Front brakesHydraulic Disc
- Rear brakesHydraulic Disc

## Suspension

- Front Suspension Double A-Arm
- Suspension Travel - Front (cm/in.) 25,4 / 10
- Rear Suspension Double A-Arm
- Suspension Travel - Rear (cm/in.) 25,4 / 10

## Type Approval

- Type Approvals L7e / LOF / T3S / T3C
- Number of Seats 2

## Towing / Hauling

- Rack Capacity - Front (kg/lbs.) 45,4 / 100
- Rack/Box Capacity - Rear (kg/lbs.) 22,7 / 50
- L7e [kg] 181
- LOF [kg] braked 840
- LOF [kg] unbraked 181
- T3S [kg] braked 978
- T3S [kg] unbraked 489
- T3C [kg] braked 978
- T3C [kg] unbraked 489

## Additional Specs

- Alternator Capacity (amps) 28
- Fuel Capacity (lt./gal.) 20,1 / 5,3
- Speedometer Digital
- Odometer Digital
- Tire Front 25x8-12
- Tire Rear 25x10-12
- Features adjustable suspension  
alum. rims  
automotive-style paint  
front mounted 3.000 lbs. / 1.360 kg winch  
fully independent suspension  
passenger seat  
Powersteering  
rear hitch w. 50mm ball (no electric wiring)  
rear swaybar  
Duramatic automatic transmission  
On-the-fly 2WD/4WD  
Front differential lock

**Electronic fuel injection (EFI)**  
**Dynamic engine braking**  
**3-in-1 System**